

CLAIMS

What is claimed is:

- 59 a1
1. A slider for a disk drive, comprising:
 - a supporting structure having a top surface with a pocket and a plurality of protrusions protruding from the pocket where a protruding end of the protrusions forms an air bearing surface; and
 - a coating on the top surface of the supporting structure other than the protrusions, the coating being formed from a material that is softer than the supporting structure.
 2. The slider of claim 1 wherein the coating is located on the pocket of the top surface of the supporting structure.
 3. The slider of claim 1 wherein the coating is located on one or more corners of the top surface of the supporting structure.
 4. The slider of claim 1 wherein the coating is located along lateral sides edges of the top surface of the supporting structure.
 5. The slider of claim 1 wherein the coating is sputtered onto the top surface of the supporting structure.
 6. The slider of claim 1 wherein the material of the coating is a metal.

20/5/20

[illegible]

1 8 A slider for supporting a transducer for use in a disk drive, comprising:
2 a support structure having a top surface with a pocket with a plurality of air
3 bearing protrusions, and at least one shock-absorbing protrusion protruding from the
4 pocket where a protruding end of the air bearing protrusions form an air bearing
5 surface, and the shock-absorbing protrusion comprises a material that is softer than
6 the supporting structure.

1 9. The slider of claim 8 wherein the shock-absorbing protrusion is located at a
2 corner of the top surface of the supporting structure.

1 10. The slider of claim 8 wherein the shock-absorbing protrusion is located along
2 lateral sides edges of the top surface of the supporting structure.

1 11. The slider of claim 8 wherein the shock-absorbing protrusion is sputtered onto
2 the top surface of the supporting structure.

1 12. The slider of claim 8 wherein the shock-absorbing protrusion comprises a
2 material selected from the group consisting of metals and polymers.

Sub
C13

1 13. A magnetic recording device for reading or writing magnetically, comprising:

- 2 (a) a disk comprising a substrate and a metallic magnetic layer;
- 3 (b) a head support on a slider for magnetically reading data to or writing
- 4 data from the magnetic layer on the disk, the slider comprising a support structure
- 5 having a top surface with a pocket and a plurality of air bearing protrusions and at
- 6 least one shock-absorbing protrusion protruding from the pocket where a protruding
- 7 end of the air bearing protrusions form an air bearing surface, and the shock-
- 8 absorbing protrusion comprises a material that is softer than the supporting structure;
- 9 (c) a motor operable to rotate the disk; and
- 10 (d) an actuator connected to the slider for moving a head across the disk.

11 14. The device of claim 13 wherein the shock-absorbing protrusion is located at a

12 corner of the top surface of the supporting structure.

13 15. The device of claim 13 wherein the shock-absorbing protrusion is located

14 along lateral sides edges of the top surface of the supporting structure.

15 16. The device of claim 13 wherein the shock-absorbing protrusion is sputtered

16 onto the top surface of the supporting structure.